



MARTEK

ACOPLAMIENTO RAPIDOS STORZ

Acoplamiento Storz

Calidades: Aluminio, Latón

Medidas: Desde DN-3/4 A DN-4" (19-100 mm.)



Racor Storz con cola de manguera dentada

Cola de manguera de acoplamiento Storz

NPS:	Cola de manguera [mm]:	Lug distancia
3/4"	19mm	44
1"	25mm	31 - 44 - 66
1 1/4"	32mm	44 - 66
1 1/2"	38mm	51 - 66
2"	52mm	66-81-89
	60mm	66
2 1/2"	65mm	81 - 89
	70mm	81
3"	75mm	89
	80mm	89
	90mm	105 - 133
4"	100mm	115 - 133
	110mm	133



Storz ajustando la tapa en blanco

Tapa antipolvo de acoplamiento Storz

Distancia de orejeta [mm]:
31
44
51
66
81
89
105
115
133
148
160
220



Acoplamiento Storz con rosca hembra

Storz roscado hembra

Tamaño:	Distancia de orejeta: (mm)
1"	31 - 44 - 51 - 66
1 1/4"	44 - 51 - 66
1 1/2"	51 - 66
2"	51-66-81-89
2 1/2"	66-81-89
3"	81 - 89 - 105
4"	115 - 133
4 1/2"	133
5"	148
6"	160 - 188
10"	278



Acoplamiento Storz con rosca macho

Storz roscado macho

Tamaño:	Distancia de orejeta: (mm)
1"	31 - 44 - 66
1 1/4"	44 - 66
1 1/2"	51 - 66
2"	51-66-81-89
2 1/2"	66-81-89
3"	81 - 89
4"	115 - 133
5"	160
6"	188
8"	220